


NASA Contractor Report 194989

ICASE Report No. 94-79



ICASE

ON THE REMOVAL OF BOUNDARY ERRORS CAUSED BY RUNGE-KUTTA INTEGRATION OF NON-LINEAR PARTIAL DIFFERENTIAL EQUATIONS

Saul Abarbanel
David Gottlieb
Mark H. Carpenter

DEFENSE TECHNICAL INFORMATION CENTER
Approved for public release;
Distribution Unlimited

19941221 046

Contract NAS1-19480
September 1994

Institute for Computer Applications in Science and Engineering
NASA Langley Research Center
Hampton, VA 23681-0001



Operated by Universities Space Research Association

ON THE REMOVAL OF BOUNDARY ERRORS CAUSED BY RUNGE-KUTTA INTEGRATION OF NON-LINEAR PARTIAL DIFFERENTIAL EQUATIONS¹

Saul Abarbanel¹

Department of Mathematical Sciences
Division of Applied Mathematics
Tel-Aviv University
Tel-Aviv, ISRAEL

David Gottlieb¹

Division of Applied Mathematics
Brown University
Providence, RI 02912

Mark H. Carpenter

Theoretical Flow Physics Branch
Fluid Mechanics Division
NASA Langley Research Center
Hampton, VA 23681-0001

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

ABSTRACT

It has been previously shown that the temporal integration of hyperbolic partial differential equations may, because of boundary conditions, lead to deterioration of accuracy of the solution. A procedure for removal of this error in the linear case has been established previously.

In the present paper we consider hyperbolic p.d.e's (linear and non-linear) whose boundary treatment is done via the SAT-procedure. A methodology is present for recovery of the full order of accuracy, and has been applied to the case of a 4th order explicit finite difference scheme.

¹This research was supported by the National Aeronautics and Space Administration under NASA Contract No. NAS1-19480 while the authors were in residence at the Institute for Computer Applications in Science and Engineering (ICASE), NASA Langley Research Center, Hampton, VA 23681. The second author was supported also by AFOSR 93-0090 ARPA grant N00014-91-J-4016 and NSF grant DMS - 9211820

1. Introduction

Currently there is a growing interest in long time integration for solving problems in areas such as aero-acoustics, electro-magnetics, material-science and others. This necessitates, ([1]), working with higher order (4th order accuracy and above) schemes. Often the methodology of choice is to semi-discretize the equations by applying a high order (4th and above) spatial difference operator and then advance temporally using single level multi-stage Runge-Kutta integrators. This raises the question of how to supply boundary values at the intermediate stages of the R-K integrations. In the case of hyperbolic p.d.e's that means the imposition of the time dependent conditions at the inflow boundary.

The conventional (and intuitively natural) way of imposing inflow boundary conditions at the intermediate stages is to use the "appropriate" value of the boundary data, $g(t)$, at each stage. Thus, for example, at a stage corresponding to $t + (\Delta t/2)$, one would impose $g(t + \Delta t/2)$.

In a previous paper ([2]), it was shown that the procedure described above, when applied to hyperbolic p.d.e's with time dependent b.c.'s, reduces the accuracy near the inflow boundary to first order and thus the overall accuracy cannot exceed $O(\Delta x^2)$. This conclusion is independent of the order of accuracy of the spatial difference operator.

One way of avoiding the dilemma of what boundary values one should supply at the intermediate stages, is to advance the R-K integration without imposing any intermediate values, but rather obtain the intermediate boundary values from the numerical solution operator. However, this approach has the disadvantage of reducing substantially the stability limit (e.g., the allowable time step is reduced by a factor 2 in the case of 4th order classical R-K with a 4th order spatial derivative operator), hence rendering it less than attractive.

In ([2]) a general methodology was presented in the case of linear p.d.e.'s for the correct imposition of the intermediate stage boundary values so that the scheme recovers its full formal accuracy. This was expounded in detail for the case of the classic 4th order R-K with a hyperbolic 4th order spatial difference operator. It was also shown there that in the non-linear case (e.g. hyperbolic conservation laws) this methodology was applicable to R-K integration up to 3rd order. For R-K methods of 4th order and above we were not able to extend the theoretical approach described in ([2]).

In this paper we address anew the issue of how to deal with the non-linear case. We present a methodology for retaining the full accuracy even in the non-linear case. The application of this methodology involved numerical determination of free parameters in contradistinction to the linear procedure described in ([2]). We find for example, that in the 4th order classical R-K integrator with 4th order explicit spatial derivative operator, the full accuracy is retained without

any reduction in the allowable time step.

The new procedure is demonstrated for hyperbolic problems where the boundary conditions are satisfied by using the SAT approach ([3]). The motivation for doing so is that the SAT procedure is the only one that prevents temporal growth not present in the true solution of a system of p.d.e.'s. Section 2 describes how to apply correctly the intermediate SAT boundary conditions in the case of a linear problem. In Section 3 we cover the non-linear case.

2. The Linear Case

In this section we analyze the effect of imposing the inflow boundary conditions in the conventional way when the discretization algorithm employs the SAT approach (see ([3])). The SAT is a penalty type method that was constructed so as to ensure that the numerical solution will not include temporal growth which is not of a physical origin. This is achieved by mimicking the energy estimate of the p.d.e.

Recall that we are considering the following hyperbolic problem (see ([3])):

$$\frac{\partial u}{\partial t} + \frac{\partial u}{\partial x} = 0, \quad 0 \leq x \leq t, t \geq 0 \quad (2.1)$$

$$u(0, t) = g(t) \quad (2.2).$$

The SAT formulation for the semi-discrete version of (2.1) - (2.2), based on a uniform grid, is

$$\frac{dv_i(t)}{dt} = \left(\frac{1}{h} D \vec{V}(t) \right)_i - \frac{1}{h} \tau \vec{\sigma} (v_0(t) - g(t)), \quad i = 0, 1, \dots, N; \quad t \geq 0 \quad (2.3)$$

where $\vec{V} = [v_0, v_1, \dots, v_N]^T$ is the semi-discrete approximation that converges to $u(x_i, t)$ at the spatial grid points x_i (for stable discretizations); and $\frac{1}{h} D$ is the differential matrix representation of the derivative operator $(-\frac{\partial}{\partial x})$. The vector $\vec{\sigma}$ depends on the differentiation matrix $\frac{1}{h} D$, and on the energy norm used in bounding the error. It is determined as described in ([3]); see the discussion after equation (6) therein.

The demonstration of accuracy deterioration will be shown for the four stage "classical" RK algorithm, which is one of the most commonly used RK time advancing schemes. For the analysis to make sense we assume that the spatial discretization is at least fourth order accurate.

The above mentioned four stage RK integrator is implemented as follows:

$$V^{(1)} = V^{(n)} + \frac{\lambda}{2} D V^{(n)} - \frac{\lambda}{2} \tau \vec{\sigma} [v_0^{(n)} - g(t)] \quad (2.4)$$

$$V^{(2)} = V^{(n)} + \frac{\lambda}{2}DV^{(1)} - \frac{\lambda}{2}\tau \bar{\sigma} \left[v_0^{(1)} - g\left(t + \frac{\Delta t}{2}\right) \right] \quad (2.5)$$

$$V^{(3)} = V^{(n)} + \lambda DV^{(2)} - \lambda \tau \bar{\sigma} \left[v_0^{(2)} - g\left(t + \frac{\Delta t}{2}\right) \right] \quad (2.6)$$

$$\begin{aligned} V^{(n+1)} = & V^{(n)} + \frac{\lambda}{6}D[V^{(n)} + 2V^{(1)} + 2V^{(2)} + V^{(3)}] \\ & - \frac{\lambda}{6}\tau \bar{\sigma} \left\{ [v_0^{(n)} - g(t)] + 2 \left[v_0^{(1)} - g\left(t + \frac{\Delta t}{2}\right) \right] + 2 \left[v_0^{(2)} - g\left(t + \frac{\Delta t}{2}\right) \right] \right. \\ & \left. + [v_0^{(3)} - g(t + \Delta t)] \right\}. \end{aligned} \quad (2.7)$$

To check for accuracy we substitute for the $V^{(n)}$ the exact values $u(x_i, t)$, and in particular $v_0^{(n)} = g(t)$. Note from eq. (2.4), that on the boundary (using the differential equations (2.1), (2.2))

$$v_0^{(1)} = v_0^{(n)} - \frac{\Delta t}{2} \left(\frac{\partial}{\partial x} u \right)_0 = g(t) + \frac{\Delta t}{2} g'(t). \quad (2.8)$$

Thus in eq. (2.7), we have for the term $v_0^{(1)} - g\left(t + \frac{\Delta t}{2}\right)$,

$$v_0^{(1)} - g\left(t + \frac{\Delta t}{2}\right) = \left[g(t) + \frac{\Delta t}{2} g'(t) \right] - g\left(t + \frac{\Delta t}{2}\right) = 0(\Delta t^2). \quad (2.9)$$

Thus $V^{(n+1)} - V^{(n)}$ is at best $0(\Delta t^2)$, and not $0(\Delta t^5)$ as expected from the R-K scheme used.

In this linear case, the remedy proposed in the previous paper, ([2]), works here as well. In particular, eqs. (2.4) -(2.7) take the following form:

$$V^{(1)} = V^{(n)} + \frac{\lambda}{2}DV^{(n)} - \frac{\lambda}{2}\tau \bar{\sigma} [v_0^{(n)}(t) - g(t)] \quad (2.10)$$

$$V^{(2)} = V^{(n)} + \frac{\lambda}{2}DV^{(1)} - \frac{\lambda}{2}\tau \bar{\sigma} \left[v_0^{(1)} - g(t) - \frac{\Delta t}{2}g'(t) \right] \quad (2.11)$$

$$V^{(3)} = V^{(n)} + \lambda DV^{(2)} - \lambda \tau \bar{\sigma} \left[v_0^{(2)} - g(t) - \frac{\Delta t}{2}g'(t) - \frac{\Delta t^2}{4}g''(t) \right] \quad (2.12)$$

$$\begin{aligned} V^{n+1} = & V^n + \frac{\lambda}{6}D \left[V^{(n)} + 2V^{(1)} + 2V^{(2)} + V^{(3)} \right] \\ & - \frac{\lambda}{6}\tau \bar{\sigma} \left\{ [v_0^{(n)} - g(t)] + 2 \left[v_0^{(1)} - g(t) - \frac{\Delta t}{2}g'(t) \right] \right. \\ & + 2 \left[v_0^{(2)} - g(t) - \frac{\Delta t}{2}g'(t) - \frac{\Delta t^2}{4}g''(t) \right] \\ & \left. + \left[v_0^{(3)} - g(t) - \Delta t g' - \frac{\Delta t^2}{2}g'' - \frac{\Delta t^3}{4}g''' \right] \right\}. \end{aligned} \quad (2.13)$$

It is readily verified that $V^{(n+1)} - V^{(n)} = 0(\Delta t^5)$, as required.

3. The Non-Linear Case

For the sake of simplicity we consider first the scalar conservation law p.d.e.

$$\frac{\partial u}{\partial t} + \frac{\partial f(u)}{\partial x} = 0, \quad 0 \leq x \leq 1; \quad t \geq 0 \quad (3.1)$$

$$u(0, t) = g(t). \quad (3.2)$$

In general, for any spatial discretization (whether explicit or implicit) the semi-discrete form of (3.1) - (3.2) is:

$$\frac{dV}{dt} = \frac{1}{h} Df(V) - \frac{1}{h} \tau \bar{\sigma} [v_0 - g(t)]. \quad (3.3)$$

Using the notation of reference ([3]),

$$D = -P^{-1}Q \quad (3.4)$$

where $\frac{1}{h}D$ is the differentiation matrix representing the differential operator, $(-\frac{\partial}{\partial x})$; composed of the explicit part Q and the inverse of the implicit part P . For a fully explicit spatial differentiation, $P = I + B$, where B differs from zero only at the two diagonal corners (see examples of P and Q in ([4])).

The vector $\bar{\sigma}$, again using the notation of [], is given by

$$\bar{\sigma} = ha(u_0)g_{00}P^{-1}H^{-1}S \quad (3.5)$$

where $a(u_0) = (\frac{\partial f}{\partial u})_{x=0}$, and g_{00} is twice the value of the left upper corner element of HQ . For the definition of the matrix H see Assumption I in [1]. The parameter τ is determined from stability consideration to be $\tau \geq 1$, see ([3]).

Next we demonstrate that writing the classical 4th order RK for eq. (3.3), using the linear "fix" as in equations (2.10) - (2.13), does not yield the required 4th order accuracy:

$$V^{(1)} = V^{(n)} + \frac{\lambda}{2} Df(V^{(n)}) - \frac{\lambda}{2} \tau \bar{\sigma} [v_0^{(n)} - g(t)] \quad (3.5)$$

$$V^{(2)} = V^{(n)} + \frac{\lambda}{2} Df(V^{(1)}) - \frac{\lambda}{2} \tau \bar{\sigma} \left[v_0^{(1)} - g(t) - \frac{\Delta t}{2} g'(t) \right] \quad (3.6)$$

$$V^{(3)} = V^{(n)} + \lambda Df(V^{(2)}) - \lambda \tau \bar{\sigma} \left[v_0^{(2)} - g(t) - \frac{\Delta t}{2} g'(t) - \frac{\Delta t^2}{4} g''(t) \right] \quad (3.7)$$

$$\begin{aligned}
V^{(n+1)} = & V^{(n)} + \frac{\lambda}{6} D[f(V^n) + 2f(V^{(1)}) + 2f(V^{(2)}) + f(V^{(3)})] \\
& - \frac{\lambda}{6} \tau \sigma \left\{ [v_0^{(n)} - g(t)] + 2 \left[v_0^{(1)} - g(t) - \frac{\Delta t}{2} g'(t) \right] \right. \\
& + 2 \left[v_0^{(2)} - g(t) - \frac{\Delta t}{2} g'(t) - \frac{\Delta t^2}{4} g''(t) \right] \\
& \left. + \left[v_0^{(3)} - g(t) - \Delta t g' - \frac{\Delta t^2}{2} g'' - \frac{\Delta t^3}{4} g''' \right] \right\}.
\end{aligned} \tag{3.8}$$

Again, when checking accuracy, we take $V^{(n)} = u(x_i, t)$, and in particular $v_0^{(n)} = g(t)$; and also $\frac{1}{h} Df(V^n) = -\frac{\partial}{\partial x} f(u) + 0(\Delta t^4)$. With these preliminaries we get immediately from equation (3.5)

$$v_0^{(1)} = v_0^n - \frac{\Delta t}{2} \frac{\partial}{\partial x} f(u)_0 = g(t) + \frac{\Delta t}{2} \frac{\partial}{\partial t} (u)_0 = g(t) + \frac{\Delta t}{2} g'(t). \tag{3.9}$$

Note that this is the same as in the linear case, see eq. (2.8). Thus with $v_0^{(n)} = g(t)$ and with equation (3.9) we can supply, for the purpose of accuracy checking, the correct values of $v^{(n)}$ and $v_0^{(1)}$. When we look at eq. (3.6), using the above results, the governing non-linear p.d.e., and simple Taylor's expansion, we have:

$$\begin{aligned}
V^{(2)} = & V^{(n)} + \frac{\lambda}{2} Df \left[V^{(n)} + \frac{\lambda}{2} Df(V^n) \right] \\
= & V^{(n)} - \frac{\Delta t}{2} \frac{\partial}{\partial x} f \left[u - \frac{\Delta t}{2} \frac{\partial}{\partial x} f(u) + 0(\Delta t^5) \right] = V^n - \frac{\Delta t}{2} \frac{\partial}{\partial x} f \left[u + \frac{\Delta t}{2} \frac{\partial u}{\partial t} + 0(\Delta t^5) \right] \\
= & V^{(n)} - \frac{\Delta t}{2} \frac{\partial}{\partial x} \left\{ f(u) + \frac{\Delta t}{2} \frac{\partial f}{\partial u} \frac{\partial u}{\partial t} + \frac{\Delta t^2}{8} \left(\frac{\partial^2 f}{\partial u^2} \right) \left(\frac{\partial u}{\partial t} \right)^2 + 0(\Delta t^3) \right\} \\
= & V^{(n)} - \frac{\Delta t}{2} \left\{ \frac{\partial f}{\partial x} + \frac{\Delta t}{2} \frac{\partial}{\partial t} \left(\frac{\partial f}{\partial x} \right) \right\} + 0(\Delta t^3) \\
= & u - \frac{\Delta t}{2} \left[-u_t - \frac{\Delta t}{2} u_{tt} \right] + 0(\Delta t^3).
\end{aligned} \tag{3.10}$$

So finally we have on the boundary

$$v_0^{(2)} = g(t) + \frac{\Delta t}{2} g'(t) + \frac{\Delta t^2}{4} g''(t) + 0(\Delta t^3). \tag{3.11}$$

It follows from (3.11) that the "penalty" term in (3.8) introduces an error of (Δt^3) . Since the coefficient of (Δt^3) , $[f_{uu}(u_t)^2]_0$, cannot generally be expressed as a function of $g(t)$ and

its derivatives, it is very difficult to remedy the situation. Thus the “linear procedure” fails at the third RK stage.

We now propose a methodology to deal with the RK integration of non-linear hyperbolic conservation laws. We first present this procedure in the case of the classic 4th order R-K scheme. Our starting point is the observation that the “linear-procedure” yields the required accuracy for $v_0^{(n)}$ and $v_0^{(1)}$. The idea is to use at each stage a linear combination of the “linear” SAT, or penalty, terms used (3.5) and (3.6). The 4th order classic RK stages will thus be:

$$V^{(1)} = V^{(n)} + \frac{\lambda}{2} Df(V^n) - \frac{\lambda}{2} \alpha \bar{\sigma} [v_0^{(n)} - g(t)] \quad (3.12)$$

$$V^{(2)} = V^{(n)} + \frac{\lambda}{2} Df(V^{(1)}) - \frac{\lambda}{2} \beta \bar{\sigma} [v_0^{(1)} - g(t) - \frac{\Delta t}{2} g'(t)] - \frac{\lambda}{2} \gamma \bar{\sigma} [v_0^{(n)} - g(t)] \quad (3.13)$$

$$V^{(3)} = V^{(n)} + \lambda Df(V^{(2)}) - \lambda \delta \bar{\sigma} [v_0^{(n)} - g(t)] - \lambda \epsilon \bar{\sigma} [v_0^{(1)} - g(t) - \frac{\Delta t}{2} g'(t)] \quad (3.14)$$

$$V^{(n+1)} = V^{(n)} + \frac{\lambda}{6} D[f(V^n) + 2f(V^{(1)}) + 2f(V^{(2)}) + f(V^{(3)})] \quad (3.15)$$

$$- \frac{\lambda}{6} \mu \bar{\sigma} [v_0^{(n)} - g(t)] - \frac{\lambda}{3} \nu \bar{\sigma} [v_0^{(1)} - g(t) - \frac{\Delta t}{2} g'(t)]$$

where the free parameters $\alpha, \beta, \gamma, \delta, \epsilon, \mu$, and ν will be chosen so as to maximize the allowable time step. It is clear from the previous discussion that the system (3.12) - (3.15) maintains the 4th order accuracy. There remains the question of whether the CFL stability condition deteriorates, in comparison to the conventional application of R-K, equation (2.4) - (2.7). It is also clear that the optimal choice of the free parameters α, \dots, ν varies with the spatial discretizations (i.e. the differentiation matrix D) and boundary closures. One checks that the absolute values of the eigenvalues of the amplification matrix resulting from (3.12) - (3.15) should not exceed unity. We carried out this procedure (using Mathematica Software) in the case of an explicit 4th order algorithm with 3rd order boundary closures. In this case $H = I$, and the matrices P and Q can be found in section (9.1) of reference [3]. With the following values of the free parameters, $\alpha = \beta = -\epsilon = 1$, $\delta = 2$, $\mu = 0$, $\nu = 3$, $\gamma = -0.37$, the CFL condition becomes $\lambda \leq 2.1$. This is the same restriction on the time step, Δt , as one has in the linear problem using the “conventional”, i.e. less accurate, boundary values with or without the SAT-term.

4. Conclusions

In summary, we have in (3.12)-(3.15) a 4th order RK scheme, applied to a non-linear p.d.e., which maintains the overall 4th order accuracy without any decrease in the allowable time step. The extension to a system of hyperbolic p.d.e.'s is quite straight forward using the SAT-system approach delineated in ([3]).

References

- [1] O. Kreiss and J. Oliger, Comparison of Accurate Methods for the Integration of Hyperbolic Problems, *Tellus* V24, (1972), pp.199-215.
- [2] M.H. Carpenter, D. Gottlieb, S. Abarbanel and W.S. Don , The Theoretical Accuracy of Runge-Kutta Time Discretizations for the Initial Boundary Value Problem: A Study of the Boundary Error. To appear in *SIAM Journal on Scientific Computing*, ICASE report 93-83.
- [3] M.H. Carpenter, D. Gottlieb, and S. Abarbanel, Time-Stable Boundary Conditions for Finite-Difference Schemes Solving Hyperbolic Systems: Methodology and Application to High-Order Compact Schemes, NASA Contractor Report 191436, ICASE Report No. 93-9, March 1993. To appear in *JCP*.
- [4] M.H. Carpenter, D. Gottlieb, and S. Abarbanel, Stable and Accurate Boundary Treatments for Compact, High Order Finite Difference Schemes, *Applied Numer. Math.*, 12 (1993) pp. 55-87.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY(Leave blank)	2. REPORT DATE September 1994	3. REPORT TYPE AND DATES COVERED Contractor Report		
4. TITLE AND SUBTITLE ON THE REMOVAL OF BOUNDARY ERRORS CAUSED BY RUNGE-KUTTA INTEGRATION OF NON-LINEAR PARTIAL DIFFERENTIAL EQUATIONS		5. FUNDING NUMBERS C NAS1-19480 WU 505-90-52-01		
6. AUTHOR(S) Saul Abarbanel David Gottlieb Mark H. Carpenter				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Institute for Computer Applications in Science and Engineering Mail Stop 132C, NASA Langley Research Center Hampton, VA 23681-0001		8. PERFORMING ORGANIZATION REPORT NUMBER ICASE Report No. 94-79		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-0001		10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA CR-194989 ICASE Report No. 94-79		
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Michael F. Card Final Report To be submitted to Journal of Computational Physics				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 64		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) It has been previously shown that the temporal integration of hyperbolic partial differential equations may, because of boundary conditions, lead to deterioration of accuracy of the solution. A procedure for removal of this error in the linear case has been established previously. In the present paper we consider hyperbolic p.d.e.'s (linear and non-linear) whose boundary treatment is done via the SAT-procedure. A methodology is present for recovery of the full order of accuracy, and has been applied to the case of a 4th order explicit finite difference scheme.				
14. SUBJECT TERMS 4th order Runge-Kutta, Time-dependent boundary conditions, hyperbolic p.d.e.'s		15. NUMBER OF PAGES 9		
		16. PRICE CODE A03		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	

NSN 7540-01-280-5500